

## External Plastic Cabinet S

For one2clean



The image shows the External plastic cabinet S for 3 – 18 inhabitants

### Benefits

- ✓ Flexible application of the proven one2clean control cabinet in a plastic external column
- ✓ Weather-resistant plastic
- ✓ Edge seal for complete sealing over the ground
- ✓ High corrosion protection for the electrical parts
- ✓ Good value for money
- ✓ Easy assembly
- ✓ No foundation necessary

### External plastic cabinet S

For 3 – 18 inhabitants (up to 2,700 l/d)

Order no. 107990

### Technical data

For air compressors	XP 60 / 80, HP 100-200
Upstream fuse	Bt6A (provided by customer)
Voltage supply	230 V AC ± 20 %, 50 Hz
IP	IP44
Relative air humidity	10 to 95 %
Temperature range	-25°C to +50°C
Total weight	7 kg (15.4 lbs)
Connecting line	via two-pin earthed plug

### Compatibility

one2clean 3 – 18 PE

### Accessories for small wastewater treatment systems



#### Sampling point, internal

For two- and multitank systems ≤ 60 PE

Order no. 107170

#### Odour-tight empty pipe seal DN 100 for systems compatible with SBR-hose packages up to 28 PE

- Ensures no air, humidity or gas escapes from conduit pipe
- No need for PU seals
- Clean and professional solution

Order no. 107887



## External Plastic Cabinet M

For one2clean/one2clean plus



The image shows the External plastic cabinet M for 3 – 18 inhabitants with LED warning light

### Benefits

- ✓ Easy access for the maintenance fitter
- ✓ Function checking is simple as the control unit is located immediately next to the system
- ✓ Ideal solution for large distances from the house (20 m)
- ✓ Flexible use of the proven GRAF EPP control cabinet in the External plastic cabinet L (size 3 – 18 inhabitants)
- ✓ Lockable housing in sturdy, weather-resistant plastic
- ✓ Integrated double power socket for easy maintenance
- ✓ No foundation necessary

### External plastic cabinet M

For 3 – 18 inhabitants (up to 2,700 l/d)

Order no. 107773

### Technical data

For air compressors	LA 45 – 80, XP 60/80, HP 100 – 200
Upstream fuse	Bt6A (provided by customer)
Voltage supply	230 V AC ± 20 %, 50 Hz
IP	IP44
Relative air humidity	10 to 95 %
Temperature range	-25°C to +50°C
Total weight	10 kg (22 lbs)
Connecting line	via two-pin earthed plug

### Compatibility

one2clean 3 – 18 PE

one2clean plus 3 – 18 PE



#### GRAF Handbook of Wastewater Treatment

More information about wastewater can be found in our Handbook of Wastewater Treatment.

